



Configuration:

LR-4200-150 Intelligent DSP RF Receiver (150 MHz)

Product Overview:

The LR-4200-150 receiver from Listen Technologies offers outstanding audio clarity and quality with the best range and reception in its class.

Part of our Intelligent Digital Signal Processing (iDSP) line, the LR-4200-150 is the smallest device of its kind, resulting in a compact unit that is easy for users to carry, wear, and use. An integrated neck loop/lanyard offers hands-free convenience, and the DSP loop driver offers an improved listening experience for anyone with a T-coil-equipped hearing aid. Dual 3.5mm output jacks also allow receivers to be shared between users.

Each receiver is also equipped with a micro USB connection, making it easy for venues to charge and update the units via any standard USB port.

The LR-4200-150 incorporates advanced Lithium-ion rechargeable batteries that offer long life and reliable power, allowing each receiver to provide outstanding performance even during longer presentations or conferences. Charge status, along with channel information and volume level, are easy to read on the integrated OLED display.

The LR-4200-150 is an outstanding receiver choice for any venue looking to offer convenient, reliable assistive listening with best-in-class clarity.

Highlights:

- High-performance 150 MHz RF receiver offering best-in-class sensitivity and 20dB less noise than other devices
- Integrated neck loop/lanyard with DSP loop driver for an enhanced T-coil listening experience
- Smallest device of its kind makes it easier to wear and use and for venues to dispense, store and maintain
- OLED display showing channels, battery status, channel status, volume level, and more
- Limited lifetime warranty with hassle-free support
- Lanyard and belt clip options offer convenient and discreet choices for the end user
- Advanced rechargeable battery technology eliminates the costs and hassles associated with frequent battery replacement
- Designed for single-channel applications

Includes:

One (1) LR-4200-150 Intelligent DSP RF Receiver (150 MHz)* *The LR-4200-150 comes with a quick start guide and a non-proprietary field replaceable Lithium-ion battery.

Product Specification: Intelligent DSP RF Receiver (150MHz)	
Audio	
System Distortion	< 2% total harmonic distortion (THD) at 80% deviation
Output/s	Two (2) 3.5 mm (0.14 in.) connectors, unbalanced, 0 dBu nominal output level, 16 mW maximum, impedance 32 ohm

Product Specification: Intelligent DSP RF Receiver (150MHz)	
System Frequency Response	50 Hz - 15 kHz (± 3 dB)
System Signal to Noise Ratio	SQ enabled 80 dB, SQ disabled 60 dB
Controls	
User Controls	Power, up/down volume
Programming	Via software and USB port
Set-up Controls	Press and hold up/down volume buttons for 5 seconds to enter channel adjust, use up/down to select channel
Indicators	
LEDs	Flashes when batteries are low or to indicate charging, solid when fully charged
Display	Channel designation, battery level, unit number, charging status
RF	
Frequency Range	150.850 - 152.350 MHz
Number of Channels	6 wide band, 26 narrow band
Sensitivity	.6uV typical, 1 uV maximum for 12 dB sinad
Squelch	Programmable in 20 steps, automatic on loss of RF signal
Antenna Type	Uses ear phone/neck loop lanyard and short ear phone cable or standard earphone cable
Power	
Power Supply	Micro USB connector, 5 V, 500 mA
Battery Type	Lithium Ion 3.7 Vdc, 1200 mAh
Battery Life	8 Hours of continuous use
Battery Charging Time	Fully charged in 2.5 Hours
Physical	
Color	Black
Unit Weight with Batteries	2.40 oz. (68 g)
Shipping Weight	3.20 oz. (91 g) with 1.0 lbs. (454 g) minimum
Dimensions (H x W x D)	3.75 x 2.00 x 0.64 in. (9.6 x 5 x 1.7 cm)
Unit Weight	1.60 oz. (45 g)
Dimensions with Belt Clip	3.75 x 2.00 x 0.80 in. (9.6 x 5.0 x 2.1 cm)
Environmental	
Temperature - Operation	14 to 104 °F (-10 to 40 °C)
Temperature - Storage	(-)4 to 122 °F (-20 to 50 °C)
Relative Humidity	0 to 95% relative humidity, non-condensing
Compliance	
Marks and Approvals	RCM, RoHS